

V420-C4 / V430-C4 Cable Label Print & Apply Machine

Cable label print & apply system — specification sheet

Bilingual Edition
中英对照版

产品参数介绍 Introduction of product parameters

型 号 Model	V420-C4/V430-C4	CPU特性 CPU	双核32位处理器 32-bit CPU
分 辨 率 Resolution	203dpi/306dpi	贴标速度 Labeling speed	1200个/小时 1200 pcs/h
打印宽度 Printing width	7-104mm		
打印高度 Printing height	10-60mm	尺寸 Size	535mm(L)×390mm(W)×950mm(H)
最大介质外径 Max roll diameter	200mm	重量 Weight	29KG
介质宽度 Media width	10-125mm	指令集 Programming language	NPL 兼容TPCL/TSPL NPL compatible with TPCL TSPL
线缆直径 Wire harness diameter	1-20mm		
动能 Kinetic energy	气动 Pneumatic	存 储 器 Storage	RAM:32MB FLASH:256MB
标签尺寸 Label size	长度不大于 130mm Length not exceeding 130mm	打 印 头 Print head	平压式 flat-pressed
贴标方式 Labeling method	夹贴 Clip stick	打印方式 Print type	直热式/热转印 Thermal/thermal transfer
贴标方向 Labeling direction	垂直顶贴 Top		
操作温度 Operational temperature	5°C - 40°C	通讯接口 Connection	USB, 串口, 网络端口, IO端口 USB, serial, network, IO
储存温度 Storage temperature	-20°C - 60°C		
操作湿度 Operational humidity	25% ~ 85% RH (无凝露) 25%-85% RH (non-condensing)	二维码类型 TDcode type	QR.code, DataMatrix, PDF417 Maxicode, MicroPDF417
外部信号 Digital I/O interface	输入1: 触发打印 Inputs1: start printing 输出1: 打印完成 Outputs1: printing finished 输入2: 触发贴标 Inputs2: start labeling 输出2: 贴标完成 Outputs2: labeling finished	储存湿度 Storage humidity	10% ~ 90% RH (无凝露) 10%-90% RH (non-condensing)
碳带内径 Ribbon core diameter	25.6mm	条码类型 Barcode type	Code39, Code39Ext, Code128, ITF25 CODE25, MATRIX25, EAN8/13, UPC A/E, CODABAR, CODE93, CODE ONE CODE 49, CODE 16K
碳带长度 Ribbon length	300m		
碳带宽度 Ribbon width	25-115mm		
可用字体 Font	NMARK0, NMARK1, NMARK2, NMARK3, NMARK4, NMARK5, 宋体, 黑体 Times Roman, Arial, Letter Gothic, OCR-A/B, Courier, Prestige Elite	附 件 Attachment	USB通讯线, 直流适配器, 产品说明书 USB, DC adapter, Instruction

适应材料: 格拉辛底纸, 底纸厚度不大于50u, 面层厚度不小于50u。

Applicable materials: glassine base paper, with a thickness of no more than 50u for the base paper and no less than 50u for the surface layer.

V420-C4/V430-C4



Cable mark print apply labeling machine

线缆标识打印贴标机



自动化的时
代来啦!

Automation Time
It's coming!



V420-C4 / V430-C4 Cable Label Print & Apply Machine

Cable label print & apply system — specification sheet

Specifications

Parameter	Value
Model	V420-C4 / V430-C4
Resolution	203 dpi / 306 dpi
Printing width	7–104 mm
Print height	10–60 mm
Max roll diameter	200 mm
Media width	10–125 mm
Wire harness diameter	1–20 mm
Drive type	Pneumatic
Label size	Length not exceeding 130 mm
Labeling method	Clip stick
Labeling direction	Vertical top labeling
Operating temperature	5 °C – 40 °C
Storage temperature	–20 °C – 60 °C
Operating humidity	25% – 85% RH (non-condensing)
Digital I/O interface	Input 1: start printing; Input 2: start labeling; Output 1: printing finished; Output 2: labeling finished
Ribbon core diameter	25.6 mm
Ribbon length	300 m
Ribbon width	25–115 mm
Fonts	NMARK0, NMARK1, NMARK2, NMARK3, NMARK4, NMARK5, SimSun, SimHei, Times Roman, Arial, Letter Gothic, OCR-A/B, Courier, Prestige Elite
CPU	Dual-core 32-bit CPU
Labeling speed	1200 pcs/h
Dimensions	535 mm (L) × 390 mm (W) × 950 mm (H)
Weight	29 kg
Programming language	NPL, compatible with TPCL/TSPL
Storage	RAM: 32 MB FLASH: 256 MB
Printhead	Flat-pressed
Print mode	Direct thermal / Thermal transfer
Interface	USB, serial port, network port, IO port
2D code types	QR code, DataMatrix, PDF417, Maxicode, MicroPDF417
Barcode types	Code 39, Code 39 Ext, Code 128, ITF25, Code 25, Matrix 25, EAN-8/13, UPC A/E, Codabar, Code 93, Code One, Code 49, Code 16K
Accessories	USB cable, DC adapter, user manual

Application

- Cable identification / marking labels.

Applicable materials: glassine liner, liner thickness not more than 50 μm and face-stock thickness not less than 50 μm.