

产品参数介绍 Introduction of product parameters

型号 Model	V420-C3/V430-C3	CPU特性 CPU	双核32位处理器 32-bit CPU
分辨率 Resolution	203dpi/306dpi	贴标速度 Labeling speed	1200个/小时 1200 pcs/h
打印宽度 Printing width	7-104mm	尺寸 Size	535mm(L)×390mm(W)×950mm(H)
打印高度 Printing height	10-60mm	重量 Weight	29KG
最大介质外径 Max roll diameter	200mm	指令集 Programming language	NPL 兼容TPCL/TSPL NPL compatible with TPCL TSPL
介质宽度 Media width	10-125mm	存储器 Storage	RAM:32MB FLASH:256MB
线束直径 Wire harness diameter	1-20mm	打印头 Print head	平压式 flat-pressed
动能 Kinetic energy	气动 Pneumatic	打印方式 Print type	直热式/热转印 Thermal/thermal transfer
标签尺寸 Label size	长度不大于 130mm Length not exceeding 130mm	通讯接口 Connection	USB, 串口, 网络端口, IO端口 USB, serial, network, IO
贴标方式 Labeling method	夹贴 Clip stick	二维码类型 TDcode type	QR.code, DataMatrix, PDF417 Maxicode, MicroPDF417
贴标方向 Labeling direction	垂直顶贴 Top	储存湿度 Storage humidity	10% ~ 90% RH (无凝露) 10%-90% RH (non-condensing)
操作温度 Operational temperature	5°C - 40°C	碳带内径 Ribbon core diameter	25.6mm
储存温度 Storage temperature	-20°C - 60°C	碳带长度 Ribbon length	300m
操作湿度 Operational humidity	25% ~ 85% RH (无凝露) 25%-85% RH (non-condensing)	碳带宽度 Ribbon width	25-115mm
外部信号 Digital I/O interface	输入1: 触发打印 Inputs1:start printing 输出1: 打印完成 Outputs1:printing finished 输入2: 触发贴标 Inputs2:start labeling 输出2: 贴标完成 Outputs2:labeling finished	条码类型 Barcode type	Code39, Code39Ext, Code128, ITF25 CODE25, MATRIX25, EAN8/13, UPC A/E, CODABAR, CODE93, CODE ONE CODE 49, CODE 16K
可用字体 Font	NMARK0, NMARK1, NMARK2, NAMR3, NMARK4, NMARK5, 宋体, 黑体 Times Roman, Arial, Letter Gothic, OCR-A/B, Courier, Prestige Elite	附件 Attachment	USB通讯线, 直流适配器, 产品说明书 USB, DC adapter, Instruction

适应材料: 格拉辛底纸, 底纸厚度不大于50u, 面层厚度不小于50u。
Applicable materials: glassine base paper, with a thickness of no more than 50u for the base paper and no less than 50u for the surface layer.

V420-C3/V430-C3

Cable mark print apply labeling machine

线缆标识打印贴标机



自动化的时代来啦!

Automation Time
It's coming!

